



Super Fluoroether Grease

- *Features super advanced Fluoroether Synthetic formula.*
- *Provides superior resistance to acids and solvents – even radiation.*
- *Offers exceptional oxidative & thermal stability in hostile conditions.*

TRUST Save Money
OMEGA Enhance Performance
TO Extend Service Life

SPECIAL FEATURES

Omega 28 Super Fluoroether Grease is quality engineered for "Mission Impossible - Mission Critical" lubrication applications.

- **Omega 28** features a super advanced Fluoroether Synthetic formula for today's toughest operating environments.
- **Omega 28** is virtually indestructible and provides superior resistance a wide range of acids and solvents – even radiation!
- **Omega 28** offers exceptional oxidation and thermal stability characteristics in even the most hostile conditions. Thermal degradation will generally not occur until direct contact temperatures exceeding 500°F (260°C) are encountered.

OUTSTANDING PROPERTIES

Omega 28 is the super fluoroether synthetic grease that:

- Resists even hydrocarbon fuels while providing exceptional long-lasting lubrication qualities.
- Is compatible with most plastics and elastomeric seal materials.
- Is compatible with most plastics and elastomeric seal materials.
- Stays where applied for outstanding dependability.

Omega 28 is formulated to withstand direct contact with :

- Nitrogen Tetroxide • Unsymmetrical Dimethylhydrazine • Oxygen • Turbine Fuel • Ethyl Alcohol • Boiling Nitric Acid • Boiling Sulfuric Acid • Aniline • Ammonia • Molten Sodium Hydroxide • Hydrazine • Diethylenetriamine • Fluorine • up to 90% Hydrogen Peroxide.

USE FOR

Omega 28 text can be used for a wide range of applications that demand the highest performance lubrication, including:

- Aeronautical Equipment • Drug and Pharmaceuticals Production • Computer Chip and Components Production • Electroplating Plants • Fertilizer Factories • Hospitals and Clinics.

Use **Omega 28** for lubricating pipe threads for high-pressure oxygen pipes and for seals, threads, joints and stems used for liquids, gas and strenuous vacuum service environments.

Omega 28 is also ideal for use on plastics and ceramics.



Omega

The Ultimate Lubricant

ITW PPFK reserves the right to modify or change this product for purposes of improving its performance characteristics.
© 2016 ITW PP & F Korea Limited

The Omega Trade Mark is the property of ITW Inc., and is used under licence by ITW PP & F Korea Limited.



The information contained in this publication is to the best of our knowledge and accurate at the time of issue in October, 2016